

CSI-2000-UX10 for Getac UX10







CSI-2000-UX10 Grab & Go Charge and Networked wired Security Cabinet designed for up to 7 Getac UX10 with or without Hand straps. Dimensions 21.8" W 12.7" D x 32" H. Wall mounting brackets included.

Rating: Not Rated Yet

Price

7 Days
★ ★ ★ ★ ★

[Ask a question about this product](#)

Description

CSI-2000 UX10Tablet Cabinet

For Getac UX10 Fully Rugged Tablets

Description

The CSI-2000-UX10 Grab and Go cabinet is designed specifically for up to 7 Getac UX10 ruggedized tablets with or without Handstraps. The grab-and-go style cabinet allows the user to take-out and return tablets without having to worry about plugging them in. Tablets are connected to the cabinet through the proprietary Pogo connector allowing A/C power and network access. To ensure the devices are charged and up to date with software patches the cabinet can accommodate an optional 8 port Cisco switch. This small form factor cabinet is ideal for areas with limited space and can be attached to a wall using the supplied mounting bracket.

Features

- Supports up to 7 Getac UX10 Fully Rugged Tablets with or without Handstraps
- Grab-and-Go design makes removal and return fast and easy
- Proprietary Pogo connector eliminates cable mess and connection failure
- Power and Network (Cat 6 Wiring) provided to each slot/ dock
- Top compartment can accommodate a Cisco 8 port switch
- Hinged door with single keyed lock
- Door window allows visibility of power lights on tablets
- Thermostatically controlled fan in top lid

Cabinet Specifications

Cabinet is designed to only be used with Getac UX10 Fully Rugged

Tablets

- Model Number: CSI-2000-UX10 Cabinet Dimensions: 32"H x 18.65"W x 12.2"D
- Cabinet Weight (Empty): 75 lbs
- Cabinet Max Weight: 120 lbs
- Operating Temperature: 10 - 32+ degrees Celsius
- Wall Mount: Wall Mounting Brackets Supplied

Cabinet Power Specifications

Cabinet Power Supply is UL Approved

- Voltage: 110VAC or 240VAC
- Current: 12 amps
- Circuit Breaker: 15A (max)
- Frequency: 50-60Hz
- Overload Protection: Automatic Shutdown and Restart
- Overheat Protection: Automatic Shutdown and Restart

Docking Slot Specifications

- Docking Station Connector: Proprietary Pogo 24-pin Connector
- Power: 19v DC
- Network: 10/100/1000 base-T Ethernet

Fan System Specifications

- Fan Size:

Dual 120mm x 120mm

- Airflow: 108 CFM / 126 m³/h (@ 1,350 RPM)

- Noise Level: 0.3 Sone (@ 1,350 RPM)

- Thermostat: Activated by temperature controller when above 86 Deg F. Foam replaceable debris filters available for each fan

Where to Buy Charge Solutions Inc. Products in the United States

Contact Charge Solutions Inc. direct to obtain pricing, GSA Pricing Available.

Charge Solutions Inc.

855-423-3435

info@chargesolutionsinc.com

